

State Certificate of Authorization Engineering & Land Surveying No. 24GA27969200 Landscape Architecture No. MH000043

Engineers Landscape Architects Land Surveyors Planners Environmental Specialists

STORMWATER IMPACT REPORT

FOR

BLOCK 468.01 – LOT 24.01 50 ATRIUM DRIVE TOWNSHIP OF FRANKLIN SOMERSET COUNTY, NEW JERSEY

January 2022

Prepared For:

Applicant: 50 Atrium Drive, LLC 50 Atrium Dive Somerset, NJ 08873

Prepared By:

THE REYNOLDS GROUP, INC. 575 ROUTE 28, SUITE 110 RARITAN, NEW JERSEY 08869

F. Mitchel Ardman, P.E. NJ License No. 34317

TABLE OF CONTENTS

<u>Section</u>		<u>Item</u>	<u>Page</u>		
I.		Project Summary	1		
II.		Discussion of Stormwater Impact			
	A. B. C.	Stormwater Quantity Stormwater Quality Groundwater Recharge Stormwater Conveyance System Design	1 2 2		
III.	2				
APPENDIX A Figure Figure Figure		2 Soils Map - (USDA Web Soil Survey)			

APPENDIX A CONVEYANCE SYSTEM CALCULATIONS

Computations for Sizing of Proposed Stormwater Conveyance Pipes

MAP POCKET Drainage Area Maps

DA-1 Inlet Drainage Area Map

I. PROJECT SUMMARY

The applicant proposes to construct a one story, approximately 70,300 sf warehouse addition to the existing building along with associated site improvements on Lot 24.01, Block 468.01 located along Atrium Drive / Davidson Avenue. The 11.86-acre tract currently includes a one-story main warehouse building with an office area along with a large parking lot and loading docks. The total impervious coverage from these existing site features is 6.76 acres.

The proposed warehouse addition will be placed over the existing paved parking lot, with the final site impervious area of 6.74 acres. The result is a net <u>reduction</u> of impervious area of 0.017 acres (736 sf).

The existing site drains to a retention pond in the northern section of the property, along Route 287. Since there is no increase in impervious area, there will be no impact to this existing pond.

II. DISCUSSION OF STORMWATER IMPACT

A. STORMWATER QUANTITY

CUMULATIVE SITE ANALYSIS:

. The breakdown of site surface coverage is as follows:

Existing Conditions:

Impervious Surfaces:

Pavement 199,762 sq. ft.
Roof 82,421 sq. ft.
Sidewalk 12,230 sq. ft.
Total: 294,413 sq. ft.

56.99% Impervious Coverage

Proposed Conditions:

Impervious Surfaces:

Pavement 130,808 sq. ft.
Roof 152,721 sq. ft.
Sidewalk 10,148 sq. ft.
Total: 293,677 sq. ft.

56.85% Impervious Coverage

Since the proposed improvements will not increase the amount of on-site impervious area (reduction proposed), nor reduce the runoff time of concentration, the overall stormwater runoff from the site will not increase as a result of this project. Stormwater quantity control measures are therefore not required.

B. STORMWATER QUALITY

The existing building footprint is 82,421 sf. The proposed cumulative roof area is 152,721 sf., therefore, the building impervious area will increase by approximately 70,300 sf. The amount of pavement on-site will decrease by 68,954 sf (1.58 acres) square feet. Since the project will result in a significant decrease in impervious motor vehicle surface, no water quality measures are required.

C. GROUNDWATER RECHARGE

Since the proposed site development will result in a <u>decrease</u> in impervious area for the 11.86-acre property, the amount of groundwater recharge provided on-site will, therefore, increase as part of this proposal. As such, no structural groundwater recharge measures are required.

In summary, the proposal will have no adverse impacts on the quantity, quality and groundwater recharge volume of the stormwater runoff from the site.


III. STORMWATER CONVEYANCE SYSTEM DESIGN

Calculations supporting the design of the proposed stormwater conveyance system are in Appendix B of this report. The inlet flows were computed using the Rational Method and cumulative pipe flows are compared to pipe capacity. A 25-year design storm was utilized for the new parking lot inlet system and a 100-year design storm was used from the existing inlet to the existing retention pond (that existing pipe run shall be removed and upgraded to handle the required flow). Inlet drainage areas are shown on map DA-1.

APPENDIX A

MAP FIGURES






PROPERTY STREET ADDRESS: 50 ATRIUM DRIVE ROAD, FRANKLIN, NJ



	Title: LOCATION MAP							
	Scale: NOT TO SCALE TRG Job #: 21-024	Date: 01/06/22						
	Project: 50 ATRIUM DRIVE	Sheet No.:						
ס	BLOCK 468.01, LOT 24.01 TOWNSHIP OF FRANKLIN SOMERSET COUNTY, NEW JERSEY	1						





575 Route 28 Suite 110 Raritan, N.J. 08869 Tele 908-722-1500

	Title: U.S.G.S TOPO MAP - BOUND	BROOK QUAD		
	Scale: NOT TO SCALE TRG Job #: 21-024	Date: 01/06/22		
	Project: 50 ATRIUM DRIVE	Sheet No.:		
0	BLOCK 468.01, LOT 24.01 TOWNSHIP OF FRANKLIN SOMERSET COUNTY, NEW JERSEY	2		





PenB - PENN SILT LOAM

RehA - REAVILLE SILT LOAM

RehB - REAVILLE SILT LOAM

RorAt - ROWLAND SILT LOAM



575 Route 28 Suite 110 Raritan, N.J. 08869 Tele 908-722-1500

litle: SOILS MAP (USDA WEB SOIL SURVEY)							
Scale: NOT TO SCALE	TRG Job #: 21-024	Date: 01/06/22					
	Sheet No.:						
TOWNSHIP OF FR	3						
	Scale: NOT TO SCALE Project: 50 ATRIUM D BLOCK 468.01, L TOWNSHIP OF FR	Scale: NOT TO SCALE TRG Job #: 21-024 Project: 50 ATRIUM DRIVE BLOCK 468.01, LOT 24.01 TOWNSHIP OF FRANKLIN SOMERSET COUNTY, NEW JERSEY					

APPENDIX B

CONVEYANCE SYSTEM CALCULATIONS

• Storm Sewer Pipe Computations



CALCULATIONS FOR STORM SEWER SYSTEM

PROJECT NAME: 50 ATRIUM DRIVE TRG #: 21-024

Page 1 of 1

STORM FREQ.: <u>25 years</u> PREPARED BY: <u>AR</u> DATE: <u>6-Jan-22</u>

100-yr at d/s end

STRUC	TURE	AREA			TOTAL	Тс		Q	PIPE	SLOPE	CAPACITY	FF VEL.	
from	to	(acres)	С	AxC	AxC	(min.)	(in/hr)	(cfs)	SIZE (in)	(%)	(cfs)	(fps)	NOTES
	7	0.73	0.89	0.65		10	5.61	3.6					
7	6				0.65	10	5.61	3.6	15	0.50	4.6	3.7	121 If RCP
	6	0.68	0.92	0.63		10	5.61	3.5					
6	5				1.28	10	5.61	7.2	18	0.60	8.1	4.6	73 If RCP
	5	0.34	0.99	0.34		10	5.61	1.9					
5	4				1.61	10	5.61	9.0	18	0.75	9.1	5.1	101 If PVC
	4	0.56	0.93	0.52		10	5.61	2.9					
4	3				2.13	10	5.61	12.0	18	1.35	12.2	6.9	80 If RCP
3	1				2.13	10	5.61	12.0	18	1.35	12.2	6.9	167 If RCP
	2	0.28	0.94	0.26		10	5.61	1.5					
2	1				0.26	10	5.61	1.5	15	1.00	6.5	5.3	36 If RCP
	1	0.52	0.9	0.47		10	5.61	2.6					
1	1A				2.86	10	5.61	16.1	24	0.75	19.6	6.4	421 If RCP
1	1A	(100 yr Storm Check) >>>			2.86	10	6.46	18.5	24	0.75	19.6	6.4	421 If RCP
1A 1B		(100 yr	Storm Ch	neck) >>>	2.86	10	6.46	18.5	24	0.75	19.6	6.4	75 If RCP
	8	0.50	0.62	0.31		10	5.61	1.7					
8	9				0.31	10	5.61	1.7	15	0.75	5.6	4.6	133 If RCP
	9	0.30	0.72	0.22		10	5.61	1.2					
9	10				0.53	10	5.61	3.0	15	1.00	6.5	5.3	39 If RCP
10	11				0.53	10	5.61	3.0	15	1.50	7.9	6.4	208 If RCP
	11	0.35	0.72	0.25	_	10	5.61	1.4					
11	EX. MH				0.78	10	5.61	4.4	24	0.43	14.8	4.7	124 If RCP

